



1915L 19-inch LCD

Touchscreen Monitor



Integrated Touch



Commercial Grade



3-Year Warranty

Product Overview

The Elo 1915L standard format touchscreen monitor is built to withstand the rigors of continuous public use with a rugged built-for-touch design. Its stylish, thin and modern look, coupled with a retail-focused feature set and is an attractive solution for commercial touchscreen monitor needs. The 1915L can be used in a wide variety of environments with its ability to register inputs from a finger, gloved hand or soft stylus with a fast and accurate response. The touchmonitor is available with Elo's industry-leading touch technologies and multiple mounting options to support most application uses.

The Elo 1915L offers multiple mounting options to ensure installation flexibility including: wall- and pole-mount via standard VESA mount patterns as well as tabletop accommodations with the use of the desktop stand. Capped through-mount holes on the base of the touchmonitor ensure table-top security.

Available with AccuTouch five-wire resistive and IntelliTouch surface acoustic wave (SAW) with an anti-glare display and Dual/Serial USB

Touchscreen sealed from dirt, dust and liquid

Removable base and VESA mounting option

1915L 19-inch Touchscreen Monitor

Specifications	
Model	1915L
Color	Dark gray
Active Display Area	14.8" x 11.9" / 376.3 mm x 301.1 mm
LCD Technology	Active matrix TFT LCD
Diagonal Size	19" / 482.6 mm
Aspect Ratio	5:4
Native Resolution	1280 x 1024
Other supported resolutions	1280 x 1024 at 60 or 75 Hz; 1152 x 864 at 75 Hz; 1024 x 768 at 60, 65, 70 or 75 Hz; 832 x 624 at 75 Hz (Mac); 800 x 600 at 56, 60, 72 or 75 Hz; 720 x 400 at 70 Hz; 720 x 350 at 70 Hz; 640 x 480 at 60, 66, 72 or 75 Hz
Number Of Colors	16.7 million
Brightness (Typical)	LCD panel: 250 nits; with AccuTouch: 200 nits; with IntelliTouch: 225 nits
Response Time (Tr + Tf) (Typical)	14 msec
Viewing Angle (Typical)	Horizontal: ±85° / 170°; Vertical: ±80° / 160°
Contrast Ratio (Typical)	1000:1
On-Screen Display (OSD)	Accessible through switches along the bottom. Controls: Menu, Up, Down, Select, Power Settings: Auto Adjust, Brightness, Contrast, H-position, V-position, Clock, Phase, Color Temperature, OSD Timeout, OSD Language, Sharpness, Recall Defaults, Information Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese Lockouts: OSD, Power
I/O	VGA DC jack AC jack USB Type B RS232 (DB-9)
Video	VGA (VGA DE-15 (DB-15) Male connector cable included) Input Video Horizontal Sync frequency range: 31.5 - 80KHz Input Video Vertical Sync (frame rate) frequency range: 56.3-75Hz
Power	Internal AC, power connector-C6 type Input voltage range: 100-240VAC, 50/60Hz Monitor input power connector: Coaxial power jack (2.0mm pin outer diameter, 6.4mm barrel inner diameter, 8.8mm Barrel depth) Monitor input power signal specifications: 12VDC +/- 5%
Power Consumption (typical)	Monitor only - ON: 12.76W, SLEEP: 1.33W, OFF: 0.30W
Mounting Options	VESA 4-hole 100mm mounting interface on rear of unit
Temperature	Operating: 0°C to 40°C / 32°F to 104°F; Storage: -20°C to 60°C / -4°F to 140°F
Humidity (non-condensing)	Operating: 20%-80%; Storage: 10%-95% (38.7° maximum wet bulb temperature)
Dimensions (W x D x H)	With Stand: 15.4" x 16.9" x 8.3" / 390 mm x 429 mm x 212 mm Without Stand (IntelliTouch): 14.1" x 16.9" x 2.54" / 359 mm x 429 mm x 64.5 mm Without Stand (AccuTouch): 14.1" x 16.9" x 2.44" / 359 mm x 429 mm x 62 mm
Shipping Dimensions	21.28" x 19.50" x 11.23" / 540 mm x 495 mm x 285 mm
Weight	Unpackaged: 17.4 lbs / 7.9 kg; Packaged: 25.8 lbs / 11.7 kg
MTBF	50,000 hours demonstrated
Warranty	3 years
Extended Warranty	4 year warranty coverage - Elo P/N: E898247 5 year warranty coverage - Elo P/N: E898449 3 year warranty coverage + AUR - Elo P/N: E898648 4 year warranty coverage + AUR - Elo P/N: E894921 5 year warranty coverage + AUR - Elo P/N: E895125
Agency approvals	Canada CUL, IC; China CCC; Europe CE; United Kingdom UKCA; Korea KCC; Taiwan BSMI; United States FCC, UL; Japan VCCI; International CB; Australia RCM; Russia EAC; Mexico NoM; RoHS, China RoHS, WEEE, REACH
What's in the Box	Touch monitor, Quick Install Guide, 3x Tie wraps, VGA cable, Touch USB cable, NA Power cable, EU Power cable, EEI Label

Ordering Information

Part Number	Technology	Surface Treatment	Interface
E607608	AccuTouch	Antiglare	Dual serial/USB
E266835	IntelliTouch	Antiglare	Dual serial/USB

Learn more about Elo at EloTouch.com.

Americas

Tel +1 408 597 8000
elosales.na@elotouch.com

Europe (EMEA)

Tel +32 16 930 136
EMEA.Sales@elotouch.com

Asia Pacific

Tel +86 (21) 3329 1385
EloAsia@elotouch.com

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo and the Elo logo are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners. © 2023 Elo Touch Solutions, Inc. All rights reserved. 23121AES00069

